

400/M tube elements



Tubing for panel mount pumps

Features and benefits

- Consistent and accurate flow rates
- Optimized tube life
- Tubing elements are optimal fitted to the design of each pump type




Technical specifications


	400/M tube elements
Wall thickness	0.06 in (1.6 mm)
Compatible pumps	400F/M1

	400/M tube elements
Material	PVC, Silicone, Thermoplastic elastomer
Connector material	Polypropylene

400/M tube elements dimensions



(one element per channel)



(one element per two channels)

Product codes

Bore/Wall	Bioprene	Tygon® E-3603	Peroxide cured Silicone	Connects to
1.6/1.6 mm	049.EF6M.E16	049.ET6M.E16	049.EH6M.E16	FTLL, see transfer connections below
2.4/1.6 mm	049.EF6M.E24	049.ET6M.E24	049.EH6M.E24	FTLL, see transfer connections below
3.2/1.6 mm	049.EF6M.E32	049.ET6M.E32	049.EH6M.E32	FTLL, see transfer connections below
4.0/1.6 mm	049.EF6M.E40	049.ET6M.E40	049.EH6M.E40	FTLL, see transfer connections below

Transfer connections

Connects to	Ordering codes
Tube bore 1.6	FTLL210-6005
Tube bore 2.4	FTLL220-6005
Tube bore 3.2	FTLL230-6005
Tube bore 4.0	FTLL240-6005
Tube bore 4.8	FTLL250-6005

Disclaimer: Watson-Marlow, Pumpsil, PureWeld, LoadSure, LaserTraceability, Bioprene and Marprene are registered trademarks of Watson-Marlow Limited. STA-PURE PCS and STA-PURE PFL and Style 400 are trademarks of WL Gore & Associates Inc. Please state the product code when ordering pumps and tubing.



wmfts.com/global
28 October 2025