

Bredel Heavy Duty 2100

Bredel Heavy Duty pumps




Hose Pumps

Features and benefits

- Heavy duty bearings: provide improved lifetime when pumping high-solid content slurries
- Window guard: extra protection for the inspection window
- Reinforced brackets: more robust design, less risk of lubricant leakage, easier maintenance
- C4H paint: enhanced durability in highly corrosive environments



Bredel Heavy Duty 2100 performance



Note: The area of continuous operation diminishes with increased product temperatures. For product temperatures >40C, the area of continuous operation reduces to the corresponding red temperature line.

1. Flow required indicates pump speed
2. Calculated discharge pressure
3. Net motor power required
4. Product temperature
5. Calculated discharge pressure
6. Maximum recommended pump speed

- Continuous duty
- Intermittent duty

* Maximum 3 hours operation followed by minimum 1 hour stop

Technical specifications

	Bredel Heavy Duty 2100
Max. flow rate continuous	72000 L/h (18997 USGPH)
Max. flow rate intermittent	108000 L/h (28496 USGPH)
Volume per revolution	40 l (10.57 USG)
Max. continuous operating speed	30 rpm
Max. intermittent operating speed	50 rpm
Max. operating pressure	16 bar (232 psi)
Max. inlet pressure	1.5 bar abs (23 psi abs)
Max. suction capability	7 mWC (276 inWC)
Suction capability (80% Flow rate)	5 mWC (197 inWC)
Operating temperature	-20 °C to 45 °C (-4 °F to 113 °F)
Fluid temperature	-20 °C to 80 °C (-4 °F to 176 °F)
Min. starting torque	5300 N m (46908 in.lbs)
Weight	6093 kg (13433 lbs)
Heavy Duty bracket weight	25.1 kg
Heavy Duty bracket weight	55.3 lbs
Window guard weight	12 kg (26.4 lbs)
Hose lubricant required	120 l (31.7 USG)
Port configurations	Down, Left, Right, Up
Bearing configuration	Heavy duty bearings or 3 std bearings
Compatible hose materials	CSM, EPDM, F-NBR, NBR, NBR for food, NR-Metering, NR-Transfer
Flange assembly type	ANSI, DIN, JIS


Please consult your Bredel representative for lower or higher temperature operation.

Allowable ambient temperature is based on pump capabilities and may be further limited by gearbox ambient capabilities.

Materials of construction

	Bredel Heavy Duty 2100
Hose material	CSM, EPDM, F-NBR, NBR, NBR for food, NR-Metering, NR-Transfer
Housing	Cast iron, ISO12944 category C4H, ISO12944 category C4M, ISO12944 category C5M
Rotor assembly	Cast iron, ISO12944 category C4M
Cover assembly	Cast iron, ISO12944 category C4M
Brackets and fasteners	Cast iron, Galvanised steel, ISO12944 category C4M, Stainless steel 316
Support frame	Galvanised steel, ISO12944 category C4H, ISO12944 category C5M, Stainless steel 316
Coupling bush	Alloy steel
Seals	Neoprene, Nitrile, Thermoplastic polyurethane
Window guard	ISO12944 category C4H, Steel

Bredel Heavy Duty 2100 dimensions



Type	A1	A2	B	C	D	E	F	G	H	ØQ	R
Bredel 2100 (mm)	*	1503	800	3	1042	199	916	1338	1415	18	180
Bredel 2100 (inches)	*	59.2	31.5	0.12	41	7.8	36.1	52.7	55.7	0.71	7.1

Disclaimer: The information contained in this document is believed to be correct at the time of publication, but Watson-Marlow Bredel BV accepts no liability for any error it contains, and reserves the right to alter specifications without prior notice. All mentioned values in this document are values under controlled circumstances at our test bed. Actual flow rates achieved may vary because of changes in temperature, viscosity, inlet and discharge pressures and/or system configuration. APEX, DuCoNite, Bioprene and Bredel are registered trademarks.



wmfts.com/global
22 August 2025