

PD100

Discharge pulsation dampener

Bredel

Hose Pumps

Features and benefits

- Increases process uptime and performance by reducing pulsation in pump and process
- Reduces discharge pulsation, lessens vibrations and eliminates pipe hammer to improve pump performance
- In-line, low maintenance set-up, suitable for any Bredel and APEX pump with hose size from 25 mm to 100 mm
- Eliminates up to 90 % of the pump discharge pulsation between 29 psi and 232 psi pressure
- Certified to meet directive 2014/68/EU by Lloyds register




Technical specifications

	PD100
Max. operating pressure	232.1 psi (16 bar)
Storage temperature	-40 °F to 158 °F (-40 °C to 70 °C)
Product temperature	14 °F to 176 °F (-10 °C to 80 °C)
Assembly weight	321.9 lbs (146 kg)

Materials of construction

	PD100
Hose material	CSM, EPDM, NBR, NR
Housing assemblies	Carbon steel
O-ring	NBR
Flange materials	Galvanized steel, Stainless steel 316
Inserts	PP (polypropylene), PVC, PVDF, Stainless steel

PD100 dimensions



Dimensions in mm (for DIN flanges)							Dimensions in inches (for 150# ANSI flanges)									
A	B	C	C	n x N	L	M	A	B	C	C	n x N	L	M			
Dampener Type	Pump Type			SS	PVC PVDF PP		DIN flange size				SS				ANSI flange size	
PD100	Bredel 280	324	1356	8	48	8 x 18	160	80	12.8	53.4	0.31	1.89	4 x 3/4	6	3	
PD100	Bredel 100	324	1356	3	48	8 x 18	180	100	12.8	53.4	0.12	1.89	8x3/4	7 - 1/2	4	
PD100	Bredel 2100	324	1356	3	48	8 x 18	180	100	12.8	53.4	0.12	1.89	8x3/4	7 - 1/2	4	

Product codes

Replacement hose element			Part number
Hose Type	Material	Colour code	PD/100
NR	Natural rubber	Purple	28-P100020
NBR	Nitrile rubber	Yellow	28-P100040
EPDM	EPDM	Red	28-P100075
CSM	CSM	Blue	28-P100070

The material of the inner liner of the hose determines the hose type. Each hose type is marked by a unique colour code.
For ordering codes and information on pulsation dampeners and inserts please contact your Bredel representative.

Disclaimer: The information contained in this document is believed to be correct at the time of publication, but Watson-Marlow Bredel BV accepts no liability for any error it contains, and reserves the right to alter specifications without prior notice. All mentioned values in this document are values under controlled circumstances at our test bed. Actual flow rates achieved may vary because of changes in temperature, viscosity, inlet and discharge pressures and/or system configuration. APEX, DuCoNite, Bioprene and Bredel are registered trademarks.



wmfts.com/global
10 December 2025